

WHAT IS CLAIMED IS:

1. A coupling for enabling interconnection between a pressurized toilet flush unit and a toilet tank outlet, said  
5 pressurized toilet flush unit comprising a depending threaded spud with a mounting flange thereabout, said coupling comprising:

a gasket for providing a seal between said mounting flange and a toilet tank floor;

10 an adapter for centering the spud in said toilet tank outlet; and

a spud nut for causing centering of the adapter.

2. The coupling according to claim 1 wherein said  
15 adapter includes a collet with an inside diameter sized for snugly receiving the threaded spud and an outer diameter for snugly fitting the tank outlet and a centered flange having a diameter greater than a diameter of the toilet tank outlet.

20 3. The coupling according to claim 2 further comprising a sponge gasket for sealing between the adapter and said a toilet bowl.

4. A coupling for enabling interconnection between a  
25 pressurized toilet flush unit and a toilet tank outlet, said pressurized toilet flush unit comprising a depending threaded spud with a mounting flange thereabout, said coupling comprising:

a gasket for providing a seal between said mounting flange and a toilet tank floor;

an adapter for centering the spud in said toilet tank outlet said adapter having an expandable collet; and

5 a spud nut for compressing and centering the adapter against said toilet tank floor within the outlet.

5. The coupling according to claim 4 wherein said collet has an inside diameter sized for snugly receiving the  
10 threaded spud and an outer diameter for snugly fitting the tank outlet and a centered flange having a diameter greater than a diameter of the toilet tank outlet.

6. The coupling according to claim 5 further comprising  
15 a sponge gasket for sealing between the centered flange and a toilet bowl.